

SAFETY DATA SHEET

DELTA

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME DELTA
INTERNAL ID C100
APPLICATION Solvent Degreaser.
SUPPLIER ARROW CLEANING & HYGIENE SOLUTIONS
RAWDON ROAD
MOIRA, SWADLINCOTE
DERBYSHIRE
DE12 6DA
01283 221044
EMERGENCY 0777 8505 330
FAX 01283 225731
e-mail:sales@arrowchem.com

2 HAZARDS IDENTIFICATION

Repeated exposure may cause skin dryness or cracking. Harmful: may cause lung damage if swallowed.

CLASSIFICATION (1999/45) Xn;R65. R66.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	265-149-8	64742-47-8	60-100%	Xn;R65. R66.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

Rinse mouth thoroughly. DO NOT INDUCE VOMITING! Get medical attention.

SKIN CONTACT

Wash skin thoroughly with soap and water. Use suitable lotion to moisturise skin.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam, carbon dioxide or dry powder. DO NOT use water if avoidable.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Provide ventilation and confine spill. Do not allow runoff to sewer. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Collect with absorbent, non-combustible material into suitable containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Provide good ventilation.

STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area.

DELTA

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	WEL		1000 mg/m3			

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



HAND PROTECTION

Chemical resistant gloves required for prolonged or repeated contact. Use protective gloves made of: Rubber, neoprene or PVC.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

HYGIENE MEASURES

Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear liquid		
COLOUR	Colourless to pale yellow		
ODOUR	Mild of solvents		
RELATIVE DENSITY	0.81 @20°C	FLASH POINT (°C)	> 65°C CC (Closed cup).

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions. Avoid: Heat, sparks, flames.

11 TOXICOLOGICAL INFORMATION

MEDICAL SYMPTOMS

EYES AND MUCOUS MEMBRANES. Irritation of eyes and mucous membranes. NOSE. Irritation of nose due to vapour or dust contact. RESPIRATORY SYSTEM. Upper respiratory irritation. SKIN. Skin irritation. DIGESTIVE SYSTEM. Gastrointestinal symptoms, including upset stomach. NERVOUS SYSTEM. Headache. Dizziness.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).
	No transport warning sign required.

15 REGULATORY INFORMATION

LABELLING

DELTA



Harmful

CONTAINS

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

RISK PHRASES

R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES

S35	This material and its container must be disposed of in a safe way.
S37	Wear suitable gloves.
S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

DETERGENT LABELLING

$\geq 30\%$	Aliphatic hydrocarbons
$< 5\%$	Anionic surfactants

UK REGULATORY REFERENCES

C.H.I.P. The Chemicals (Hazard Information and Packaging for Supply) Regulations The Carriage of Dangerous Goods by Road and Rail Regulations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

Only trained personnel should use this material.

REVISION DATE 31/03/11

RISK PHRASES IN FULL

R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.